

**ASC#  
102082**



## **Warren<sup>®</sup> Multi-Vehicle Synthetic Blend ATF**

---

**WARREN MULTI-VEHICLE SYNTHETIC BLEND ATF** is a new generation automatic transmission fluid recommended for use in automobile and truck transmissions, power-shift transmissions and other types of service requiring Ford MERCON<sup>®</sup>V, MERCON<sup>®</sup>, DEXRON<sup>®</sup> III-H or Allison C-4 automatic transmission fluid. It is approved for use in Voith Transmissions. Approved for ZF applications TE-ML 03D, 04D, 14B, 16L & 17C.

**WARREN MULTI-VEHICLE SYNTHETIC BLEND ATF** is also recommended for service fill in Mercon, Chrysler, Honda/Acura, Hyundai, Jeep, Mercedes-Benz, Mitsubishi (Diamond SP-II or SP-III), Nissan (Matic D, J or K)/Infiniti, Saturn, Toyota (T-III & T-IV)/Lexus/Scion, VW/Audi, most European vehicles including BMW & Volvo, most Asian vehicles including Daewoo, Isuzu, Kia, Mazda, and Suzuki.

**WARREN MULTI-VEHICLE SYNTHETIC BLEND ATF** is not for use in transmissions requiring Ford Type F, DEXRON<sup>®</sup> VI, MERCON<sup>®</sup> SP, LV or in Continuously Variable Transmission (CVT) applications. Always consult your owner's manual where specific automatic transmission fluids are recommended.

### **Benefits**

- Outstanding resistance to oxidative and thermal breakdown
- Exceptional low temperature fluidity
- Excellent anti-wear properties.
- Stable friction properties
- Excellent gear shift quality throughout service life.

DEXRON<sup>®</sup> is a registered trademark of General Motors Corporation  
MERCON<sup>®</sup> is a registered trademark of Ford Motor Company



**Warren Oil Company, Inc**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301

***Scroll for more information***



## Warren® Multi-Vehicle Synthetic Blend ATF

**WARREN Multi-Vehicle Synthetic Blend ATF is suitable for use in the following applications:**

Allison C-4	Mercedes-Benz 236.3
Audi G-052-025-A1	Mercedes-Benz 236.5
Audi G-052-025-A2	Mercedes-Benz 236.7
Audi G-052-162 A1/A2	Mercedes-Benz 236.9
BMW LA2634	Mercedes-Benz 236.10
BMW LT71141	Mitsubishi Diamond SP-II
Dexron®	Mitsubishi Diamond SP-III
Dexron®-II	Nissan Matic-D
Dexron®-III D	Nissan Matic-J
Dexron®-III G	Nissan Matic-K
Dexron®-III H	Shell LA2634
Esso LT 71141	Subaru ATF HP
Ford Mercon®	Texaco 7045-E
Ford Mercon® V	Texaco ETL-8072 B
Honda/Acura ATF-Z1 (except CVT's)	Texaco N402
Hyundai SP-II	Toyota Type T-III
Hyundai SP-III	Toyota Type T-IV
Idemitsu K17	Voith 55.6335.32 (G607)
JWS 3309	Volvo 97340
Kia SP-II	VW G 052 990 A2 (09A)
Kia SP-III	VW G 055 025 A2 (09G)
Kia RED-1K	ZF TE-ML 03D
MAN 339 V1	ZF TE-ML 04D
MAN 339 Z1	ZF TE-ML 14A
MAN 339 Z2	ZF TE-ML 14B
Mazda M-111	ZF TE-ML 16L
Mazda ATF-MV	ZF TE-ML 17C



**Warren Oil Company, Inc**

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;  
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301

**Scroll for more information**



## Warren<sup>®</sup> Multi-Vehicle Synthetic Blend ATF

### Typical Characteristics:

WARREN MULTI-VEHICLE SYNTHETIC BLEND ATF	
Gravity, API	32.4
Density, lbs/gals	7.17
Flash, COC, °F	352
Viscosity	
@ 40 Deg. °C, cSt	32.6
@ 100 Deg. °F, cSt	7.32
Viscosity Index	200
Brookfield Viscosity	
cP @ -40°C	12,000
Color	Red
Ford MERCON <sup>®</sup> V license #	M5070301
Voith	Service bulletin #013 & 118
ZF	TE-ML 03D, 04D, 14B, 16L, 17C



### Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301