



ASC# 87474-PTO Driven Water Pump

(comes with pto shaft)

Replacement U-Joint is ASC# 31370 (series 4)

540 RPM

1-3/8" 6 spline PTO input shaft size

Inlet- 4 inches

Outlet- 4 inches

352 gallons per minute flow

23 feet Maximum Suction Lift

82 feet Total Head

15 hp to 125 hp required

Replacement Parts stocked at Agri Direct and available for shipping:

ASC#	Description	ASC#	Description
89115	INPUT SHAFT #16 FOR PTOW4	89133	MECHANICAL SEAL #43 FOR PTOW4
89116	SEAL #17 35 X 72 X 10 FOR PTOW4	89138	IMPELLER #44 FOR PTOW4
89117	INTERNAL CIRCLIP 72 #18 FOR PTOW4	89139	DIFFUSER #45 FOR PTOW4
89119	BEARING 6207 #19 FOR PTOW4	89150	WASHER 8 #46 FOR PTOW4
89120	CENTER DRIVE GEAR #20 FOR PTOW4	89151	BOLT M8 X 20 #47 FOR PTOW4
89121	BEARING 6206 #21 FOR PTOW4	89153	SEAL RING #48 FOR PTOW4
89122	GASKET #29 FOR PTOW4	89154	SEAL RING #54 FOR PTOW4
89123	BEARING 6305 #32 FOR PTOW4	89155	WHORL PLUG #55 FOR PTOW4
89124	BEARING 6306 #33 FOR PTOW4	89156	GASKET #57 FOR PTOW4
89126	SEAL 30 X 72 X 10 #35 FOR PTOW4	89161	PUMP BODY #58 FOR PTOW4
89127	OUTPUT SHAFT #36 FOR PTOW4	89162	CHECK VALVE #59 FOR PTOW4
89128	SPRING WASH 8 #37 FOR PTOW4	89163	INLET FLANGE #60 FOR PTOW4
89129	INSIDE HEX BOLT M8X25 #38 FOR PTOW4	89164	SEALED WASHER #61 FOR PTOW4
89130	PUMP COVER #40 FOR PTOW4	89165	PIPE CONNECTOR #62 FOR PTOW4
89131	BOLT M8X30 #41 FOR PTOW4	89166	SPANNER #63 FOR PTOW4
89132	SEAL RING #42 FOR PTOW4	89167	FILTER NET #65 FOR PTOW4